Status Report

Shota Izumiyama 1 Nov. 2019 mPMT-Japan meeting

New

- Solved the software issues
 - Benjamin-san fixed the WCSim and FitVertexLE
- Calculated miss-reconstruction rate
 - Energy dependency

Remind

WCSim MC generation

Detector: HK mPMT Hybrid

■ B&L: 20 k (20PC)

D.R.: 4.2 kHz

■ mPMT: 10 k (10PC)

• D.R.: 100 Hz

Particle: electrons

Energy: 3, 4, 5, 6, 8, 10, 15 MeV

of events: 10k for each energy

Position: uniform in the water tank


Direction: isotoropy

Miss-reconstruction rate


 Calculated the miss-rec. rate: how many events are reconstructed inner volume.

```
(miss-rec. rate) = \frac{(\text{# of events generated out of FV and reconstructed in FV})}{(\text{# of events generated out of FV})}
```


- FV := {volume | dWall > 150 cm}
- Calculated it at some energies: 3,4,5,6,8,10,15 MeV













Events out of FV

- I plot the reconstructed events which generated out of FV (3MeV)
- These are w/ mPMT
- Right plot shows only barrel events



Events out of FV

- I plot the reconstructed events which generated out of FV (3MeV)
- These are w/o mPMT (right plot shows only barrel).




I checked ...


- "findNLLDirectionality(...)": function giving negative log likelihood of PMT direction information
 - There are non-initialized "pmt_number_in_mpmt" for the direction information. → I added this parameter to the hits information.
 - However this change did not change the result.

"hPMTDirectionality_1D": PDF giving NLL for each PMT

group in mPMT (right fig.)

Does this make sense?





I checked ... (cont.)

- Disabled "useDirectionality": flag to use "findNLLDirectionality(...)"
 - w/ mPMT: 43/966=0.0445 (0.059 enabled)
 - w/o mPMT: 43/966=0.0445
 - ↑ 10 MeV
 - → The result w/o directionality got better.
 - Direction information is not used correctly?

Next...

Check the source code of directional information