Point Set Transformers for NOvA Multi-View Particle Segmentation

Edgar Robles, Dikshant Sagar, Alejandro Yankelevich, Jianming Bian, Pierre Baldi, for the NOvA Collaboration





Overview


- NOvA Experiment
- Machine Learning in Reconstruction Chain
- Particle Segmentation
 - Current Methods
 - Motivation for Point Set Transformers
 - Architecture and Heterogeneous Attention
 - Performance

NOVA

Overview

- Long-baseline neutrino oscillation experiment.
- Fermilab's NuMI beam is predominately ν_{μ} .
- Two functionally equivalent detectors spaced 810 km apart.
- Observe ν_{μ} disappearance and ν_{e} appearance to measure:
 - Δm_{32}^2 and mass ordering
 - $\sin^2(\theta_{23})$ and θ_{23} octant
 - CP-violating phase δ_{CP}






NOVA

Detector Technology


- Long 4cm x 6cm PVC extrusions filled with oil-based liquid scintillator. Wavelength shifter fiber through each cell leads to avalanche photodiode.
- Planes alternate in horizontal and vertical orientations to create two XZ and YZ views when viewed from the top or side.
 - These views are fundamentally 2D. The Y position of a hit in a vertical cell cannot be known and has no correspondence to any hit in a horizontal cell.




NOVA

Event Topologies

- Neutrino flavor can be determined with charged current (CC) interactions via primary lepton but not neutral current interactions (NC).
- Far detector on surface, so large cosmic ray background, but beam spill timing removes majority.





Reconstruction Chain




ML Framework

- Standard 2 x 100 x 80 images ("pixel maps") cropped around neutrino interaction used for all image-based ML at NOvA.
 - One 8-bit channel per pixel: deposited charge 0-278 MeV
- H5CAFs: Common Analysis Framework (CAF) files in ROOT format converted to HDF5 for easy ML development.
 - Includes pixel maps and truth information in format suitable for training.









EventCVN

CNN for Event Classification

- First CNN used in major HEP analysis.
 - NOvA oscillation analysis.
 Phys. Rev. Lett. 118 231801 (2017)
- 2-view Siamese CNN with MobileNetv2 architecture.









Methods paper: <u>JINST 11 P09001 (2016)</u>


ProngCVN

CNN for Prong Classification

- After prong segmentation, create pixel maps for each prong with only hits assigned to prong.
- 4-view Siamese CNN with both event and prong pixel maps.








Methods paper: Phys. Rev. D 100 073005

TransformerCVN

Transformer for Joint Event+Particle Classification


- Simultaneous predictions with weight sharing for increased interpretability.
- 2 views are treated as channels (100 x 80 x 2).




VertexCVN

CNN for Vertex Regression

- EventCVN architecture modified for vertex regression.
- Improves vertex resolution to within cell width.






Example event with split muon track due to traditional method misplaced vertex.

RegCVN

CNN for Energy Estimation

- Various ResNet CNN models for ν_e , e, and simultaneous ν_{μ}/μ energy.
- ν_{μ}/μ model takes reco. track length of longest prong as additional input for muons that leave cropped pixel map region.
- Gaussian noise added to pixel values for robustness against calibration systematic error.

Methods paper: Phys. Rev. D 99 012011




Neutrino Energy (GeV)

TransformerEE

Transformer for Energy Estimation


- Takes event-level and prong-level reconstructed variables as input.
- Transformer network replaces previous LSTM architecture.
- Gaussian noise added to energyrelated variables for robustness against calibration systematic error.
- Simultaneous ν_{μ}/μ energy predictions.


x,y,z components of the direction vector for 3D prong x,y,z components of the position vector for 3D prong transformerCVN output scores representing the likelihood that the prong was produced by a muon, electron,pion,proton,photon Estimated energy by Break Point Fitter under different particle assumptions (0: proton, 1: pion, 2: muon) BPF energy of the 3D prong shared with other prongs x,y,z components of the BPF momentum for 3D prong Prong length Number of hits in the 3D prong Number of hits of the 3D prong in XZ, Sum of the calibrated energy of all hits YZ view in the slice calE - sum(png.calE) Number of planes crossed by the 3D Number of hits in the slice prong track Sum of the calibrated energy of all hits Calorimetric energy of hits that don't associated with the 3D prong. appear in any FuzzyK prongs



Prong Segmentation

- Current method uses a fuzzy k-means clustering algorithm to reconstruct prongs: J. Phys. Conf. Ser. 664 072035 (2015).
- Clustering first applied independently to each view to create 2D prongs.
- OPALProng view-matching algorithm then creates 3D prongs.
- Motivation: Want to study whether deep learning method can improve prong segmentation without exceeding NOvA computational resource limitations.





Two **O**verlaping **PA**rtic**L**es successfully reconstructed

ML Segmentation Methods


Convolutional Neural Networks (CNNs)


- NERDProng CNN for NOvA: NPML 2020
- Image-based networks, so naturally dense
- Sparse CNNs exist, but must approximate convolutions
- Graph Neural Networks (GNNs)
 - Uses point clouds with edge connections, so naturally sparse
 - Typically need to establish rigid graph structure, usually by k-nearest neighbors (kNN)
 - Graph Attention Network (GATs) use attention mechanism for neighborhood aggregation of points
- Point Set Transformers (PSTs)

Point Set Transformers

- PST applies self-attention between points in point cloud.
- Permutation-invariant attention is appropriate for unordered point sets.
- Naturally sparse.
- Complexity grows as N², so attention operation usually limited to kNN.
- Point Transformer v3 replaced kNN with serialization of points to improve efficiency.


<u>"Point Transformer" IEEE / CVF ICCV 2021</u> <u>"Point Transformer V3: Simpler, Faster, Stronger" IEEE / CVF CVPR 2024</u>






Point Set Attention

- ullet Consider dataset represented by **event** i, **view** j, **point** k
- Edge score between two points x_k and $x_{k'}$: $w_{kk'} = Q_k K_{k'}$
- ullet Scores for all points connected to x_k normalized with softmax:




Relative Positional Encoding

- Add relative positional encoding (RPE), a Linear layer based on difference of pair's features: $RPE(x_k, x_{k'}) = Linear(x_k x_{k'})$
- Edge score is then $w_{kk'} = Q_k K_{k'} + \text{RPE}(x_k, x_{k'})$



Heterogenous Attention

- Want to share information between views from the beginning (early fusion).
- Define some inter-view distance in addition to intra-view distance, then create connections between points across views as well.
- Inter-view edge score: $w_{kk'}^{(i,j'\to j)}=Q_k^{(i,j'\to j)}K_{k'}^{(i,j'\to j)}$ where view $j'\neq j$




Pooling

- Need pooling layer to aggregate attention weights across regions separated in space.
- \bullet Pooling nearest neighbors is computationally expensive so approximate it with a grid G.
- For each square of grid G_l , simply average features of all hits within square, $v_l' = \frac{1}{|G_l|} \sum_{v_{i,i} \in G_l} v_{i,j}$
- Pooling applied separately between views.

Architecture

 Finally, apply unpooling to create U-net-like architecture, with skip connections.



Objectives

Loss Function


- Networks performs panoptic segmentation, both instance segmentation (clustering) and semantic segmentation (classification): $\mathcal{L} = \lambda \mathcal{L}_{sem} + (1 \lambda) \mathcal{L}_{ins}$
- Semantic segmentation loss is multi-class cross-entropy.
- Instance segmentation compares assignments to best possible assignments of points to segments.
 - Optimal assignment calculated with the Hungarian algorithm.

Kuhn, H. W. "The Hungarian method for the assignment problem" *Naval Research Logistics* **2** 83-97 (1955)

HPST Performance

Clustering (Instance Segmentation)


- Efficiency = % of predicted prong assigned to correct prong.
- Purity = % of true prong predicted correctly.
- Good performance, particularly in majority classes.




HPST Performance

Classification (Semantic Segmentation)





Purity (Normalized by columns)



Architecture Comparisons

 Considerable performance and resource utilization improvement compared to region-based convolution network (R-CNN), and some improvement over graph attention network (GAT).

Model	Memory usage (MiB)	Time per sample (s)	OVR AUC	Segmentation accuracy
R-CNN GAT	151.9 ± 11.950 29.10 ± 0.001	3.1449 ± 0.0660 0.3911 ± 0.0010	0.732 0.854	0.343 0.659
HPST (ours)	29.35 ± 0.559	0.4636 ± 0.0032	0.968	0.835

[&]quot;Mask R-CNN" IEEE / CVF ICCV 2017
"Graph Attention Networks" ICLR 2018

Summary

- Widespread use of machine learning in NOvA reconstruction with various approaches for use of two 2D views.
- Developed heterogeneous point set transformer model for NOvA prong segmentation, a task for which computational resource limitations previously precluded deep learning methods.
- Self-attention between hits in different views allows for information sharing between views at the hit level.
- Improvement over R-CNN and GAT models also tested.
- Network creates 2D prongs, but want to extend to 3D prongs with interpolation between views.
- More details:
 - ML4PS paper: <u>arXiv:2510.09659</u>
 - HPST for LArTPCs: <u>JINST 20 P07030 (2025)</u>